

CUSTOMER: _____

Guangzhou Shenghe Electronic Technology Co., Ltd.

SPECIFICATION FOR APPROVAL

Product Description: Aluminum Electrolytic Capacitors

Customer No.:

Specification: HP 2200 μ F/125V 30X50 125VF

Date : 9th, May, 2022

Environmental Certification: ROHS


SHDR[®]



Confirmation from Manufacturer

| Drafted by | Verified by | Approved by |
|------------|-------------|-------------|
| 姚海洋 | | 李艳林 |

Confirmation from User

| | Verified by | Approved by |
|--|-------------|-------------|
|  | | |

Manufacturer: Guangzhou Shenghe Electronic Technology Co., Ltd.

Address: No. 232 west Huifu road, Yuexiu district, Guangzhou

Contact: 0086 15920403979

keven@shdrcap.com

<http://www.shdrcap.com/>

After signing, please kindly return one copy. Thanks.

SHDR® Application Notes

When you use aluminum electrolytic capacitors ,remember the following:

1. Polarity

Regular aluminum electrolytic capacitors has polarity

Reverse voltage causes short circuit breakage of the capacitor or leakage of electrolyte .Where the polarity in a circuit sometimes reversed or unknown ,a bi-polar capacitor should be used.

2. Overvoltage

Do not apply overvoltage continuously.

When overvoltage is applied to the capacitor ,leakage current increase drastically.

Applied working voltage to capacitors should not exceed the rated working voltage of capacitor.

3. Operating temperature and life

Do not use the capacitor over the max operating temperature.

Life time of the capacitor depends on the temperature.

Generally ,life time is doubled by decreasing each temperature 10°C

Use temperature as low as possible.

4. Vent

It is recommended at least 3mm of space around the vent.

If such space is not provided ,the vent will not operate completely.

5. Ripple current

Do not apply a ripple current exceeding the rated maximum ripple current.

Applying too much ripple current to the capacitor causes great heat generation ,invites deterioration of properties of causes breakage.

Please consult factory if ripple current exceeds the specified limit.

6. Charge and discharging

Frequent and quick charge/discharge generates heat inside the capacitor ,causing increase of leakage current ,decrease of capacitor ,or breakage occasionally.

Consult us for assistance in this application.

7. Storage

When the capacitor is stored for a long time without applying voltage ,leakage current tends to increase.

This returns to normal by applying the rated voltage to the capacitor before use.

It is recommended to apply D.C .working voltage to the capacitor for 30 minutes through 1kΩ of protective series resistor ,if it is stored for more than 6 mouths .

The capacitor should be stored at a normal temperature and humidity .

8. Soldering

Improper soldering may shrink or break the insulating sleeve add/or damage the internal element as terminals and Lead wires conduct heat into the capacitor.

Avoid too high a soldering temperature and/or too long a soldering time.

9. Mechanical stress on the lead wire and the terminal

Do not apply excessive force to the lead wire and the terminal.

Do not move the capacitor after soldering to the PC board ,not carry the PC board by picking up the capacitor .For their strength ,refer to JIS C-5141 and C-5102.

10. Cleaning of boards after soldering

If the capacitor is cleaned in halogenated solvent for organic removing solder flux solvent ,the solvent may penetrate into inside of capacitor, and may generate corrosion.

11. Sleeve material

The standard sleeve material is polyvinyl-chloride.

If exposed to xylene ,toluene ,etc ,and then subjected to high heat ,the sleeve may crack .This sleeve is not insulating material.

12 .Micon' s Products meet or exceed quality standards specified by JIS-C5141W and with the reliability requirements refer to JIS-C-5102.


13 .None of ozone depleting chemicals(ODC) under the Montreal Protocol is manufacturing process of Shen Zhen Moonlight Electronic Industrial CO.,Ltd.

SHDR® HP Series

HP Series Snap-in Type 105°C

Features


- ◆ Highly reliable capacitors that withstand ripple current.
- ◆ Terminal spacing fixed at 10 mm for printed circuit board plug in.
- ◆ Aluminum case designed explosion-proof vent.
- ◆ Best for switching power supplies.



Specifications

| Item | Performance Characteristics | | | | | | | | | | | | | |
|---|--|-------------|-------|-------|--------|---------|---------|----|-----|-----|-----|-----|-----|-----|
| Operating Temperature Range | -40to+105°C | -25to+105°C | | | | | | | | | | | | |
| Rated Voltage Range | 10to100VDC | 160to450VDC | | | | | | | | | | | | |
| Capacitance Range | 330to68000 µF | 33to2200 µF | | | | | | | | | | | | |
| Capacitance Tolerance | ±20% (100Hzor120Hz, +20°C) | | | | | | | | | | | | | |
| Leakage Current (+20°C) | I ≤ 0.02CV After 5 minutes, whichever is greater measured with rated working voltage applied | | | | | | | | | | | | | |
| Dissipation Factor (tg δ) | µF \ WVDC | 10~16 | 25~35 | 50~63 | 80~100 | 160~250 | 315~450 | | | | | | | |
| | 47~390 | -- | -- | -- | 15 | 15 | 20 | | | | | | | |
| | 470~3900 | 25 | 20 | 20 | 20 | 15 | 20 | | | | | | | |
| | 4700~8200 | 35 | 30 | 30 | 25 | | | | | | | | | |
| | 10000~22000 | 40 | 35 | 30 | -- | -- | -- | | | | | | | |
| | 27000~47000 | 45 | 40 | 35 | -- | -- | -- | | | | | | | |
| | 56000~68000 | 50 | 45 | -- | -- | -- | -- | | | | | | | |
| | (100Hzor120Hz, +20°C) | | | | | | | | | | | | | |
| Low Temperature Characteristics (120Hz) | Impedance ratio , 120Hz | | | | | | | | | | | | | |
| | 电压(V) | 10 | 16 | 25 | 35 | 50 | 63 | 80 | 100 | 160 | 200 | 250 | 400 | 450 |
| | Z - 25°C / Z+20°C | 5 | 5 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| Z - 40°C / Z+20°C | 15 | 15 | 15 | 12 | 12 | 12 | 12 | -- | -- | -- | -- | -- | -- | |
| Load Life | Test conditions Duration time: 2000 hours Ambient temperature: +105°C Applied voltage : Rated Working Voltage (VDC) After test requirements: Resumed 16 hours at normal temperature Capacitance change: ≤ ±20% of the initial measured value Dissipation Factor: ≤ 200% of the initial specified value Leakage Current: ≤ The initial specified value | | | | | | | | | | | | | |
| Shelf Life | Test conditions Duration time: 1000 hours Ambient temperature: +105°C Applied voltage : None After test requirements: Resumed 16 hours at normal temperature Same limits as Load Life | | | | | | | | | | | | | |

Diagram of Dimension (Unit:mm)



Guangzhou Shenghe Electronic Technology Co., Ltd

Aluminum Electrolytic Capacitors Sample Test Report

Test Date: 2022-05-09

| | | | | | |
|-------------|--------|---------------|-------------------|--------------|----------------|
| Customer | | Series | HP | Sleeve Color | Black & Silver |
| Sample Qty | 10 pcs | Specification | 2200 μ F/125V | Part Number | |
| Test Qty | 10 pcs | Size | 30 \times 50 | PO No. | |
| ROHS Report | | | REACH Report | | |

| Items | Test Standard | AQL | | Failed Qty | Failure Reason | Conclusion |
|---------------------------------------|---|-----|----|------------|----------------|------------|
| | | Ac | Re | | | |
| Out-looking Check | Normal outlooking, Clear marks, No noticeable damage, Size compliant to diagram | 0 | 1 | 0 | / | OK |
| Capacitance (C) | 1760~2640 μ F | 0 | 1 | 0 | / | OK |
| Dissipation Factor (DF) | \leq 20 % | 0 | 1 | 0 | / | OK |
| Leakage Current(charge for 5 minutes) | \leq 5500 μ A | 0 | 1 | 0 | / | OK |
| Impedance | 3.02 A | 0 | 1 | 0 | / | OK |
| Weldability | Lead well coated | 0 | 1 | 0 | / | OK |
| Leas tensile | Normal outlooking, Clear marks, No noticeable damage, Stable Features | 0 | 1 | 0 | / | OK |
| Welding Heat Resistance | No noticeable damage, Capacitance Fluctuation \leq 5% | 0 | 1 | 0 | / | OK |
| Stress Release | Safety Vent Open, no explosion nor burning | 0 | 1 | 0 | / | OK |

Electrolytic Features Test

| Data No. | Capacitance (μ F) (120HZ) | Dissipation (tan δ) % (120HZ) | Leakage Current (μ A) ((charge for 5 minutes)) |
|-------------|--------------------------------------|---|---|
| 1 | 2059 | 11.5 | 251 |
| 2 | 2035 | 11.3 | 236 |
| 3 | 2046 | 11.0 | 248 |
| 4 | 2018 | 11.6 | 232 |
| 5 | 2109 | 11.8 | 257 |
| 6 | 2068 | 11.9 | 249 |
| 7 | 2049 | 12.0 | 265 |
| 8 | 2075 | 11.7 | 258 |
| 9 | 2058 | 11.6 | 264 |
| 10 | 2103 | 11.8 | 235 |

Inspected by: 李晓庆

Approved ed by: 曾观红